

## 09 60 00 Flooring

Revision 01/04/2019

### **Purpose:**

The Architect and/or Engineer shall incorporate the Rice specific requirements indicated in this standard's section into their design. The Architect and/or Engineer shall further produce project specifications in line with industry standards that are updated to reflect these Rice specific requirements.

### **1. Carpet**

- a. Broadloom and carpet tiles are both acceptable.
  - i. Yarn must be solution dyed Nylon.
  - ii. Must have a density factor of at least 6000
  - iii. Tufted loop pile is recommended, especially in high traffic areas.
  - iv. Woven carpets are acceptable. If broadloom, must have at least a 10 year warranty against zippering and edge ravel.
- b. Monochrome colors are discouraged. "Speckled" patterns that are not too light are recommended.
- c. Direct glue method of installation is preferred, carpet pads are not recommended.
- d. Recommended Manufacturers:
  - i. Interface
  - ii. Shaw Commercial
  - iii. Patcraft
  - iv. Mohawk
  - v. Rice Approved equal

### **2. MEP Space Floor Coating**

- a. Mechanical, Electrical and Plumbing space floors located on the first floor or in the basement shall be coated with the following system or Rice approved equal:
  1. Prime Coat: Pratt and Lambert ProHide Gold Interior/Exterior Waterborne Primer Z1001
  2. First & Second Top Coats: Krylon Acrylic Floor Coating K000Z1611 Color # IM152 Shop Floor Gray
  3. Clear Finish Coat: Seal Krete Clear Seal Gloss #606
- b. Mechanical and Plumbing Space floors on the second floor and up will be coated with the following system or Rice approved equal:
  1. DEX-O-TEX M-E Flooring NR, waterproofing mechanical floor system designed to protect occupied spaces below.
    - a. Floors: Color – 4413 Dolphin Gray
    - b. Curbs/Pads: Color – Safety Yellow